



Representative Image

Ref. No. 104055 | Cat. No. CL00A310TU**Description: CL00A310TU Contactor 3-pole 380-400V 50Hz / 480V 60Hz AC****EAN 8017018040555****Home > Power devices > Contactors > Series CL - Contactor series for General Purpose application**

Series CL & RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 380-400V 50Hz/480V 60Hz
Max.oper.current AC1 (A): 25 Max.oper.current AC3 (A): 9 Admissible power 220V/230V (kW): 2,2 Admissible power 380V/400V (kW): 4 Aux.contacts: 1NO

Descriptors

Category	Series CL - Contactor series for General Purpose application
----------	--

Specifications

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	AC
Frequency Control Voltage: AC	50 Hz 60 Hz
Terminal type	Screw terminal
Non-inductive loads AC1	25 A
Motors = 440V, 3-phase 50/60Hz AC3	9 A
Electrical endurance: # operations AC3	2 x 10 ⁶
Aux Contacts	1NO
Admissible power AC3 220V, 230V	2.2 kW
Admissible power AC3 380V, 400V	4 kW
Admissible power AC3 415V, 440V	4 kW
Admissible power AC3 500V	5.5 kW
Package (pcs)	5

Classifications

ETIM 5.0	EC000066 - Power contactor, AC switching
ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000066 - Power contactor, AC switching

Dimensions

Weight	0.295 kg
--------	----------

Publications

Title	Publication No.	Publication Type
Auxiliary contactor RL4RA (stp)		
Auxiliary contactor RL4RA (STEP format)	3D-00015	Drawings - CAD - 3D
Auxiliary contactor RL4RA (pdf)		
Auxiliary contactor RL4RA (3DPDF format)	3D-00015-PDF	Drawings - CAD - 3D
CONACL00L		
CONACL00 Side view	CONACL00L	Commercial Drawings
CONACL00T		
CONACL00 Total view	CONACL00T	Commercial Drawings
CONACL00R		
CONACL00 Rear view	CONACL00R	Commercial Drawings
CONACL00F		
CONACL00 Front view	CONACL00F	Commercial Drawings

Additional Documentation: Visit our Publication Library to find technical documentation, specifications, articles, promotional literature, 3D's,...