

Product datasheet

Specifications



UA controller, Transferpact, 380 VAC to 415 VAC 50/60Hz, 440 VAC 60Hz

29380

EAN Code: 3303430293804

Price: 1.422,00 EUR

Main

product name	UA
Product or component type	Control unit

Complementary

[Us] rated supply voltage	380...415 V AC at 50/60 Hz 440 V AC at 60 Hz
Operating mode	Stop (both normal and replacement source off) Forced operation on normal source Forced operation on replacement source Automatic operation
Interlocked device	Compact NS630b...1600 MasterPact NW Compact NS100...630 MasterPact NT
Selection modes	Circuit breaker on N Circuit breaker on R
Genset exerciser	Startup control Adjustable delayed shutdown
Test function	By pressing the test button on the front of the controller
Complementary function	Additional contact: transfer to replacement source only if contact is closed Setting of maximum startup time for the replacement source Voluntary transfer to replacement source (e.g. energy management commands) Forced normal source if replacement source not operational during peak-tariff Selection of type of normal source (single-phase or three-phase)
Local signalling	Off Fault trip On
Input type	Contacts customer voluntary order to transfer to source R
Output type	Contacts customer: indication of operation in automatic or stop mode
[Ith] conventional free air thermal current	8 A
[Ie] rated operational current	AC-12: 4 A AC 440 V AC-12: 5 A AC 380/415 V DC-13: 2 A 24 V

Environment

Standards	IEC 947-5-1
IP degree of protection	IP20 connectors: conforming to EN 60529 IP40 front: conforming to EN 60529 IP30 side: conforming to EN 60529
IK degree of protection	Front: IK07 conforming to EN 50102

Rates duty January 2016

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.6 cm
Package 1 Width	15.6 cm
Package 1 Length	17.2 cm
Package 1 Weight	1.586 kg
Unit Type of Package 2	S04
Number of Units in Package 2	6
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	10.282 kg

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	Acf791c5-78f0-4053-a7c8-a79590f1d0a3

Use Again

 Repack and remanufacture	
Take-back	No
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins